



MYREVEST

PURE ELEGANCE

MYPRIMER200

MyPrimer 200 is a water-based acrylic primer that facilitates the bonding between microcement and nonabsorbent surfaces.

It is the proper product for surfaces such as marble, terrazzo or tile. It consolidates the substrates and adjusts the absorption to allow excellent results of microcement.



Characteristics

- Adhesion promoter for non-absorbent substrates.
- Can be applied by roller or brush in one coat application. For tiles two coats are necessary.
- Water-based, non-flammable.
- Free of plasticisers, solvents, ammonia and emulsifiers.
- The product is supplied ready for use.

Consumption

Generally:

- 0,09 L/m²

Technical data

- Water based acrylic dispersion
- Appearance: Milky liquid
- Solids: 34,6 %
- pH: Between 8 and 9
- Viscosity: 12 - 13s (Ford Cup 4)
- Density at 20°C: 1,05 ± 0,01 g/mL
- Application temperature: from 5°C to 35°C
- Dry to touch: 30 minutes

Application

The substrate must be dry, clean and firm, free of grease or oil. Wait a minimum of 30 minutes and no more than 24 hours before applying the first coat of Microcement.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes. In case of contact with skin wash with soap and water. Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with the legal regulations in force. To prevent the product from drying out or thickening, close the lid after each use. This product is non-toxic, non-hazardous and non-flammable under normal handling conditions. This product does not contain any harmful substances that would require, under current regulations, any additional additional labelling measures.

Keep out of the reach of children.

Packaging

It is available in 5 litre containers.

Cleaning of tools

Tools should be washed with soap and water immediately after use.



Storage conditions

The product should be stored in its original closed packaging and protected from the weather at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, properly stored.

The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2022



**trademark
of quality
for professionals**

