



# MYREVEST

PURE ELEGANCE

## MYSEALANTPOOL

**MySealant Pool** is a one-component water-based sealer for the **MyPool** system, that creates a protective and consolidating layer.

**MySealant Pool** is formulated on the basis of acrylic copolymers in emulsion, stable in a humid environment.



### Properties

- Improves mechanical and chemical resistance.
- Stable in humid environment.
- Resistant to microcement alkalinity.
- High adhesion.
- Easy application.
- Low water absorption.
- Water-based, non-flammable.
- Permeable to water vapour.

### Application

#### As a swimming pool sealant:

Before applying **MySealant Pool** it is essential to check that the substrate is dry and free of dust. Depending on the climatic conditions and the ventilation of the working area, it is necessary to allow at least 24 hours before applying the primer to the microcement.

Apply by short pile microfibre roller in two coats, spaced 4 to 8 hours between coats.

If the sealant is applied and it rains within 7 days, this will cause staining of the sealant. It must be dried, sanded and re-varnished.

Allow a minimum period of 7 days for the sealer to reach its maximum mechanical and chemical performance.

### Consumption

**MySealantPool** (2 coats) 0,12 L/m<sup>2</sup>

### Technical data

|                         |                      |
|-------------------------|----------------------|
| Type                    | Water based emulsion |
| Appearance              | Milky liquid         |
| Solids                  | 15-20%               |
| Viscosity (Ford Cup 4)  | 10 -15 seconds       |
| Application temperature | 10°C to 25°C         |
| Dry to touch            | 20 minutes*          |

\* Depends on temperature and humidity.

### Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes. In case of contact with skin wash with soap and water. Do not swallow. If swallowed, do not induce vomiting and seek medical attention immediately.

#### The following measures are recommended:

- Good ventilation.
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with the legal regulations in force.

To prevent the product from drying out or thickening, close the lid after each use. This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.



This product does not contain any harmful substances that would require, under current regulations, any additional labelling measures. Keep out of reach of children. For more information see product safety data sheet.

## Packaging

---

It is packaged in 5 litre bottles.

## Cleaning of tools

---

Tools are washed with soap and water immediately after use.

## Storage conditions

---

The product should be stored in its original closed packaging in a dry and well-ventilated place, away from away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, if properly stored.

The product must not be used for purposes other than those specified without first having first having written instruction in its handling. It is always the responsibility of the user to take appropriate measures in order to comply with legal requirements. The Safety Data Sheets of the product are available to the professional.

Last edition: July 2023



**trademark  
of quality  
for professionals**

