



MYREVEST

PURE ELEGANCE

MYWAXPLUS

MyWax Plus is a concentrated acrylic wax for professional use with an extra glossy metallic finish. It is the product that makes more beautiful and gives a new life to microcement floors.

Unlike MyWax, this product is not diluted with water. It is applicable directly to the substrate and helps to preserve the original state of the coating over time.



Properties

- High gloss
- High resistance
- Metallic appearance
- Non-yellowing
- Easy to use

Consumption

- By machine 20 - 40 mL/m²
- By hand 30 - 50 mL/m²

Technical data

- Nature: Metallised emulsion based on acrylic polymers, PE waxes and additives
- Appearance: Opaque liquid
- Colour: White
- % solids: 23 ± 2
- pH: 9 ± 0,5
- Viscosity (Ford 4 cup): 13 ± 1s
- Density: 1,03 ± 0,01 g/mL
- Application temperature: Ambient temperature

Application

Use the product PURE, without dilution with water or any other solvent. Apply two coats of **MyWaxPlus** on the surface of the microcement already sealed, cured and completely clean, using any of the cleaners **MyCleaner** or **MyCleaner Plus**. It should be taken into account that the waxing treatment is not permanent, it is necessary to repeat the process from time to time, depending on the use of the surface.

*Important: before waxing, wait at least two weeks after the application of the **MySealant2K** to ensure proper curing and to avoid damage.

Special precautions

In case of contact with eyes, rinse with plenty of water for 15 minutes. In case of contact with skin wash with soap and water. Do not swallow. If swallowed do not induce vomiting and seek medical attention immediately.

The following measures are recommended:

- Good ventilation
- Protective goggles to prevent splashing.
- Rubber gloves.

Empty containers should be disposed of in accordance with legal regulations. To prevent the product from drying out or thickening, close the lid after each use. This product is non-toxic, non-hazardous and non-flammable under normal handling conditions.

This product does not contain any harmful substances that would require, under the current regulations, any additional labelling measures.

Keep out of reach of children.



Packaging

Available in 5-litre containers.

Cleaning of tools

Tools are washed with soap and water immediately after use.

Storage conditions

The product should be stored in its original closed and weatherproof packaging at temperatures between 10°C and 30°C, in a dry and well-ventilated place, away from sources of heat and direct sunlight. The shelf life is 1 year from the date of manufacture, properly stored.

The product should not be used for purposes other than those specified without first having instructions in writing. It is always the user's responsibility to take suitable measures in order to comply with the requirements established in local legislation. Product safety sheets are available for professionals. This technical data sheet will be valid until a new edition appears.

Last updated: June 2022



**trademark
of quality
for professionals**

